


TECHNICAL INFORMATION



Tube diameter: 32mm
Power: segments 12W - 37W
Light source: 48V
CRI: >85 / IP 20
CCT:








STANDARD FELT COLOURS



ILLUMINATED PARTS

MODEL	TUBE/ PIPE/ OTHER	NAME/ SHAPE	LIGHT SOURCE	POWER	NAME CODE
	TUBE	FIXTURE TRIGON	48V	37W	TT-FT
	TUBE	FIXTURE IPSYLON	48V	35W	TT-FY
	TUBE	S400	48V	12W	TT-S400
	TUBE	S800	48V	24W	TT-S800
	TUBE	A THIRD OF CIRCLE	48V	28W	TT-TC
	TUBE	SURFACE CONNECTOR	48V	26W	TT-S C

ADDITIONAL ELEMENTS

MODEL	TUBE/ PIPE/ OTHER	NAME/ SHAPE	MATERIAL	NAME CODE
	PANEL	IPSYLON	FILC	IA-FY-Z
	PANEL	TRIGON	FILC	TA-FY
	PANEL	STRAIGHT 400	FILC	TA-S400
	PANEL	STRAIGHT 800	FILC	TA-S800
	PANEL	IPSYLON CONCAVE	FILC	IA-FY-W
	PANEL	CORNER	FILC	TA-TC
	PANEL	END	FILC	TA-E
	PANEL	PLUG	FILC	TA-P.